

GHS-10K-01



Description

The Greyhound Server model Greyhound Server 10000 is used for supervision of medium to large sites (up to 10 000 datapoints).

Software specification

Number of connected networks	100+
Number of connected devices	1000+
Number of data points	10000+
Number of schematics	100+
Available logspace	60+ Gb
Maximum number of logged datapoints	3000 (maximum 200 samples/second)
Maximum number of samples	3+ billion
Remote patching	YES
PPP (Dial up/dial in) capabilities	YES
Craft offline site support	YES
Datacollector supported	YES
Encryption supported (SSH)	YES
Basic firewall	YES
Protocol drivers	EXOline, Modbus ASCII, Modbus RTU, SAIA, SIOX, COMLI, Carel, Compass, Omron, Johnson Controls, INU, Staefa Nico, Trend, EIB, Smart-box, SRDLink
Transport and utility drivers	RS232, Modem, TCP/IP, UDP/IP, TPipe, Simulation, Calculus

The number and size of logs and schematics are approximate values. The actual number or size depends on a number of different factors, like the schematic complexity, datatypes, log options etc.

GHS-10K-01

Hardware specification

Serial ports (RS232)	3
Serial ports (RS485)	0
Ethernet ports	0 x 10 MBit 0 x 100 MBit 2 x 1000 MBit
Power supply	220V AC
Operation environment	-
Mechanical	19" rackmount

Connections

